



### STRAIGHT SOCKET JOINT (XW)

Type XW (Xtra Wall) Inches (Metric)								
Nominal Size	Item No.	Outside Diameter		Min. Inside Diameter	Nominal Wall Thickness* (T)	Length (L)	Weight	
		Average	Tolerance				lbs/ft	kg/m
¾ (19)	07E-XW-10S	1.410 (36)	+0.056 (1.4) -0.036 (0.9)	0.910 (23)	.25 (6)	10 ft (3m)	.61	(.91)
1 (25)	10E-XW-10S	1.675 (43)	+0.056 (1.4) -0.036 (0.9)	1.175 (30)	.25 (6)	10 ft (3m)	.68	(1.01)
1¼ (32)	12E-XW-20-S	2.020 (51)	+0.056 (1.4) -0.036 (0.9)	1.520 (39)	.25 (6)	20 ft (6.1m)	.82	(1.22)
1½ (38)	15E-XW-20-S	2.260 (57)	+0.056 (1.4) -0.036 (0.9)	1.760 (45)	.25 (6)	20 ft (6.1m)	1.18	(1.76)
2 (51)	20F-XW-20-S	2.500 (64)	+0.056 (1.4) -0.036 (0.9)	2.000 (51)	.25 (6)	20 ft (6.1m)	1.26	(1.88)
2½ (64)	25F-XW-20-S	3.000 (76)	+0.056 (1.4) -0.036 (0.9)	2.500 (64)	.25 (6)	20 ft (6.1m)	1.54	(2.29)
3 (76)	30F-XW-20-S	3.500 (89)	+0.056 (1.4) -0.036 (0.9)	3.000 (76)	.25 (6)	20 ft (6.1m)	1.82	(2.71)
3½ (89)	35F-XW-20-S	4.000 (102)	+0.056 (1.4) -0.036 (0.9)	3.500 (89)	.25 (6)	20 ft (6.1m)	2.10	(3.13)
4 (102)	40F-XW-20-S	4.500 (114)	+0.056 (1.4) -0.036 (0.9)	4.000 (102)	.25 (6)	20 ft (6.1m)	2.38	(3.54)
5 (127)	50F-XW-20-S	5.500 (140)	+0.056 (1.4) -0.036 (0.9)	5.000 (127)	.25 (6)	20 ft (6.1m)	2.94	(4.38)
6 (152)	60F-XW-20-S	6.500 (165)	+0.056 (1.4) -0.036 (0.9)	6.000 (152)	.25 (6)	20 ft (6.1m)	3.50	(5.21)
8** (203)	80E-XW-20-S	8.900 (226)	+0.056 (1.4) -0.036 (0.9)	8.400 (213)	.25 (6)	20 ft (6.1m)	4.80	(7.14)
10 (254)	100F-XW-20-S	10.500 (267)	+0.056 (1.4) -0.036 (0.9)	10.000 (254)	.25 (6)	20 ft (6.1m)	5.74	(8.54)
12 (305)	120F-XW-20-S	12.500 (318)	+0.056 (1.4) -0.036 (0.9)	12.000 (305)	.25 (6)	20 ft (6.1m)	6.86	(10.21)

Note: 10 ft. (3.05 m) lengths available for 1¼" nominal size and larger.

\* Actual wall thickness is that required to meet the performance requirements for specifications. Other wall thicknesses are available by special request.

\*\* XW type conduit is also available with an inside diameter of 8.000 (203). Please contact our factory for further information.