



GASKET JOINT (ID)

Type SW (Standard Wall) Inches (Metric)										
Nominal Size	Item No.		UL/CSA Listed	Outside Diameter		Min. Inside Diameter	Nominal Wall Thickness* (T)	Length (L)	Weight	
	Belowground	Aboveground		Average	Tolerance				lbs/ft	kg/m
2 (51)	20B-SW-20-G	20D-SW-20-G	Yes	2.140 (54)	+0.028 (0.7) -0.018 (0.4)	2.000 (51)	.070 (2)	20 ft (6.1m)	0.34 (0.51)	
2½ (64)	25B-SW-20-G	25D-SW-20-G	Yes	2.640 (67)	+0.028 (0.7) -0.018 (0.4)	2.500 (64)	.070 (2)	20 ft (6.1m)	0.42 (0.63)	
3 (76)	30B-SW-20-G	30D-SW-20-G	Yes	3.140 (80)	+0.028 (0.7) -0.018 (0.4)	3.000 (76)	.070 (2)	20 ft (6.1m)	0.48 (0.71)	
3½ (89)	35B-SW-20-G	35D-SW-20-G	Yes	3.640 (92)	+0.028 (0.7) -0.018 (0.4)	3.500 (89)	.070 (2)	20 ft (6.1m)	0.60 (0.89)	
4 (102)	40B-SW-20-G	40D-SW-20-G	Yes	4.140 (105)	+0.028 (0.7) -0.018 (0.4)	4.000 (101)	.070 (2)	20 ft (6.1m)	0.79 (1.18)	
4½ (114)	45B-SW-20-G	45D-SW-20-G	Yes	4.640 (118)	+0.028 (0.7) -0.018 (0.4)	4.500 (114)	.070 (2)	20 ft (6.1m)	0.89 (1.32)	
5 (127)	50B-SW-20-G	50D-SW-20-G	--	5.140 (131)	+0.028 (0.7) -0.018 (0.4)	5.000 (127)	.070 (2)	20 ft (6.1m)	0.95 (1.41)	
6 (152)	60B-SW-20-G	60D-SW-20-G	--	6.140 (156)	+0.028 (0.7) -0.018 (0.4)	6.000 (152)	.070 (2)	20 ft (6.1m)	1.02 (1.52)	

Type MW (Medium Wall) Inches (Metric)										
5 (127)	50B-MW-20-G	50D-MW-20-G	Yes	5.192 (131)	+0.034 (0.9) -0.028 (0.7)	5.000 (127)	.096 (2)	20 ft (6.1m)	1.13 (1.68)	
6 (152)	60B-MW-20-G	60D-MW-20-G	Yes	6.192 (157)	+0.034 (0.9) -0.028 (0.7)	6.000 (152)	.096 (2)	20 ft (6.1m)	1.35 (2.01)	

Type HW (Heavy Wall) Inches (Metric)										
4 (102)	40B-HW-20-G	40D-HW-20-G	Yes	4.192 (106)	+0.028 (0.7) -0.022 (0.6)	4.000 (101)	.096 (2)	20 ft (6.1m)	0.92 (1.37)	
4½ (114)	45B-HW-20-G	45D-HW-20-G	Yes	4.692 (119)	+0.028 (0.7) -0.022 (0.6)	4.500 (114)	.096 (2)	20 ft (6.1m)	1.04 (1.55)	
5 (127)	50B-HW-20-G	50D-HW-20-G	Yes	5.220 (132)	+0.034 (0.9) -0.028 (0.7)	5.000 (127)	.110 (3)	20 ft (6.1m)	1.30 (1.92)	
6 (152)	60B-HW-20-G	60D-HW-20-G	Yes	6.220 (158)	+0.034 (0.9) -0.028 (0.7)	6.000 (152)	.110 (3)	20 ft (6.1m)	1.58 (2.35)	

* Actual wall thickness is that required to meet the performance requirements for specifications. Other wall thicknesses are available by special request.