


THERMOPLASTIC PLUG

Nominal Size	Type	IPS Item No.	ID Item No.	Weight	
				lbs	kg
¾	SW	07C-SW-26	—	0.01	(0.005)
1	SW	10C-SW-26	—	0.01	(0.005)
1¼	SW	12C-SW-26	—	0.01	(0.005)
1½	SW	15C-SW-26	—	0.01	(0.005)
2	SW	20C-SW-26	20D-SW-26	0.01	(0.005)
2½	SW	25C-SW-26	25D-SW-26	0.01	(0.005)
3	SW	30C-SW-26	30D-SW-26	0.03	(0.014)
3½	SW	—	35D-SW-26	0.03	(0.014)
4	SW	40C-SW-26	40D-SW-26	0.03	(0.014)
4	HW	40C-HW-26	40D-HW-26	0.03	(0.014)
4½	SW	—	45D-SW-26	0.05	(0.023)
4½	HW	—	45D-HW-26	0.05	(0.023)
5	MW	50C-MW-26	50D-MW-26	0.06	(0.027)
5	HW	50C-HW-26	50D-HW-26	0.06	(0.027)
6	MW	60C-MW-26	60D-MW-26	0.07	(0.032)
6	HW	60C-HW-26	60D-HW-26	0.07	(0.032)

Nominal Size	Type	Item No.	Weight	
			lbs	kg
¾	XW	07C-XW-26	0.01	(0.005)
1	XW	10C-XW-26	0.01	(0.005)
1¼	XW	12C-XW-26	0.01	(0.005)
1½	XW	15C-XW-26	0.01	(0.005)
2	XW	20D-XW-26	0.01	(0.005)
2½	XW	25D-XW-26	0.01	(0.005)
3	XW	30D-XW-26	0.03	(0.014)
3½	XW	35D-XW-26	0.03	(0.014)
4	XW	40D-XW-26	0.03	(0.014)
5	XW	50D-XW-26	0.06	(0.027)
6	XW	60D-XW-26	0.07	(0.032)




REDUCING ADAPTER

Transition adapter from ID/tubular phenolic conduit to IPS type.

Nominal Size	Type	Item No.	D1	D2	L	Weight	
						lbs	kg
2	SW	20F-SW-27	2.16 (55)	2.40 (61)	6 (152)	0.30	(0.14)
3	SW	30F-SW-27	3.16 (80)	3.52 (89)	6 (152)	0.50	(0.23)
4	SW	40F-SW-27	4.16 (106)	4.47 (114)	6 (152)	0.60	(0.27)
4	HW	40F-HW-27	4.20 (107)	4.52 (115)	6 (152)	0.70	(0.32)
5	MW	50F-MW-27	5.20 (132)	5.59 (142)	6 (152)	0.90	(0.41)
5	HW	50F-HW-27	5.24 (133)	5.63 (143)	6 (152)	1.00	(0.45)
6	MW	60F-MW-27	6.20 (157)	6.66 (169)	6 (152)	1.10	(0.50)
6	HW	60F-HW-27	6.24 (158)	6.69 (170)	6 (152)	1.20	(0.55)

Note: These are just examples of some reducing adapters. Contact Champion Fiberglass directly for other reducers.



REDUCING ADAPTER

This adapter is used for transition between different diameters of IPS phenolic conduit.

Nominal Size	IPS Item No.	D1	D2	L	Weight	
					lbs	kg
1 SW - ¾ SW	10E-SW-25-07E-SW	1.06 (27)	1.32 (34)	4 (101)	0.35	(0.16)
1¼ SW - ¾ SW	12E-SW-25-07E-SW	1.06 (27)	1.67 (42)	4 (101)	0.45	(0.20)
1¼ SW - 1 SW	12E-SW-25-10E-SW	1.32 (34)	1.67 (42)	4 (101)	0.40	(0.18)
1½ SW - ¾ SW	15E-SW-25-07E-SW	1.06 (27)	1.91 (48)	4 (101)	0.38	(0.17)
1½ SW - 1 SW	15E-SW-25-10E-SW	1.32 (34)	1.91 (48)	4 (101)	0.40	(0.18)
1½ SW - 1¼ SW	15E-SW-25-12E-SW	1.67 (42)	1.91 (48)	6 (152)	0.37	(0.17)
2 SW - ¾ SW	20E-SW-25-07E-SW	1.06 (27)	2.40 (61)	6 (152)	0.60	(0.27)
2 SW - 1 SW	20E-SW-25-10E-SW	1.32 (34)	2.40 (61)	6 (152)	0.55	(0.25)
2 SW - 1¼ SW	20E-SW-25-12E-SW	1.67 (42)	2.40 (61)	6 (152)	0.50	(0.23)
2 SW - 1½ SW	20E-SW-25-15E-SW	1.91 (48)	2.40 (61)	6 (152)	0.47	(0.21)
3 SW - 2 SW	30E-SW-25-20E-SW	2.40 (61)	3.52 (89)	6 (152)	0.65	(0.32)
4 SW - 2 SW	40E-SW-25-20E-SW	2.40 (61)	4.47 (113)	6 (152)	0.80	(0.36)
4 SW - 3 SW	40E-SW-25-30E-SW	3.52 (89)	4.47 (113)	6 (152)	0.90	(0.41)
5 MW - 3 SW	50E-MW-25-30E-SW	3.52 (89)	5.59 (142)	6 (152)	1.30	(0.59)
5 MW - 4 SW	50E-MW-25-40E-SW	4.47 (114)	5.59 (142)	6 (152)	0.85	(0.39)
6 MW - 4 SW	60E-MW-25-40E-SW	4.47 (114)	6.61 (166)	6 (152)	1.70	(0.77)
6 MW - 5 MW	60E-MW-25-50E-MW	5.59 (142)	6.61 (166)	6 (152)	1.90	(0.86)

Note: These are just examples of some reducing adapters. Contact Champion Fiberglass directly for other reducers.