

BRIDGE HANGERS, 3" ID, SW, FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

		Number of Ducts Wide												
		1		2		3		4		5		6		
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	
Number of Ducts High	1	A	2	7.50 (191)	2	12.00 (305)	2	16.50 (419)	2	21.00 (533)	2	25.50 (648)	2	30.00 (762)
		B*	2	18.25 (464)	2	18.25 (464)	2	18.25 (464)	2	18.25 (464)	2	18.25 (464)	3	18.25 (464)
		C	0	0.00 (0)	1	8.00 (203)	2	8.00 (203)	3	8.00 (203)	4	8.00 (203)	4	8.00 (203)
		D	2	3.50 (89)	3	3.50 (89)	4	3.50 (89)	5	3.50 (89)	6	3.50 (89)	7	3.50 (89)
		Weight, Lbs. (kg)	5.80 (2.6)		7.50 (3.4)		9.20 (4.2)		10.90 (4.9)		12.60 (5.7)		15.60 (7.1)	
	2	A	3	7.50 (191)	3	12.00 (305)	3	16.50 (419)	3	21.00 (533)	3	25.50 (648)	3	30.00 (762)
		B*	2	22.25 (565)	2	22.25 (565)	2	22.25 (565)	2	22.25 (565)	2	22.25 (565)	3	22.25 (565)
		C	0	0.00 (0)	1	12.00 (305)	2	12.00 (305)	3	12.00 (305)	4	12.00 (305)	5	12.00 (305)
		D	4	3.50 (89)	6	3.50 (89)	8	3.50 (89)	10	3.50 (89)	12	3.50 (89)	14	3.50 (89)
		Weight, Lbs. (kg)	7.40 (3.4)		10.00 (4.6)		12.60 (5.7)		15.20 (6.9)		17.80 (8.1)		23.20 (10.5)	
	3	A	3	7.50 (191)	3	12.00 (305)	3	16.50 (419)	3	21.00 (533)	3	25.50 (648)	3	30.00 (762)
		B*	2	25.75 (654)	2	25.75 (654)	2	25.75 (654)	2	25.75 (654)	2	25.75 (654)	3	25.75 (654)
		C	0	0.00 (0)	1	15.50 (394)	2	15.50 (394)	3	15.50 (394)	4	15.50 (394)	5	15.50 (394)
		D	6	3.50 (89)	9	3.50 (89)	12	3.50 (89)	15	3.50 (89)	18	3.50 (89)	21	3.50 (89)
		Weight, Lbs. (kg)	8.50 (3.8)		11.60 (5.3)		14.70 (6.7)		17.80 (8.1)		20.90 (9.5)		27.20 (12.4)	
	4	A	4	7.50 (191)	4	12.00 (305)	4	16.50 (419)	4	21.00 (533)	4	25.50 (648)	4	30.00 (762)
B*		2	29.75 (756)	2	29.75 (756)	2	29.75 (756)	2	29.75 (756)	2	29.75 (756)	3	29.75 (756)	
C		0	0.00 (0)	1	19.50 (495)	2	19.50 (495)	3	19.50 (495)	4	19.50 (495)	5	19.50 (495)	
D		8	3.50 (89)	12	3.50 (89)	8	3.50 (89)	20	3.50 (89)	25	3.50 (89)	28	3.50 (89)	
Weight, Lbs. (kg)		10.10 (4.6)		14.10 (6.4)		17.50 (8)		22.10 (10)		26.20 (11.9)		33.90 (15.4)		

*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar B = Support Rod C = Intermediate Rod D = Spacer Tube

BRIDGE HANGERS, 3" IPS, SW, & 3" ID, XW FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

		Number of Ducts Wide												
		1		2		3		4		5		6		
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	
Number of Ducts High	1	A	2	7.88 (200)	2	12.75 (324)	2	17.63 (448)	2	22.50 (572)	2	27.38 (695)	2	32.25 (819)
		B*	2	18.63 (473)	2	18.63 (473)	2	18.63 (473)	2	18.63 (473)	2	18.63 (473)	3	18.63 (473)
		C	0	0.00 (0)	1	8.38 (213)	2	8.38 (213)	3	8.38 (213)	4	8.38 (213)	4	8.38 (213)
		D	2	3.88 (98)	3	3.88 (98)	4	3.88 (98)	5	3.88 (98)	6	3.88 (98)	7	3.88 (98)
		Weight, Lbs. (kg)	5.90 (2.7)		7.70 (3.5)		9.60 (4.3)		11.40 (5.2)		13.20 (6)		16.30 (7.4)	
	2	A	3	7.88 (200)	3	12.75 (324)	3	17.63 (448)	3	22.50 (572)	3	27.38 (695)	3	32.25 (819)
		B*	2	23.00 (584)	2	23.00 (584)	2	23.00 (584)	2	23.00 (584)	2	23.00 (584)	3	23.00 (584)
		C	0	0.00 (0)	1	12.75 (324)	2	12.75 (324)	3	12.75 (324)	4	12.75 (324)	5	12.75 (324)
		D	4	3.88 (98)	6	3.88 (98)	8	3.88 (98)	10	3.88 (98)	12	3.88 (98)	14	3.88 (98)
		Weight, Lbs. (kg)	7.70 (3.5)		10.50 (4.8)		13.30 (6)		16.10 (7.3)		18.90 (8.6)		24.50 (11.1)	
	3	A	3	7.88 (200)	3	12.75 (324)	3	17.63 (448)	3	22.50 (572)	3	27.38 (695)	3	32.25 (819)
		B*	2	26.88 (683)	2	26.88 (683)	2	26.88 (683)	2	26.88 (683)	2	26.88 (683)	3	26.88 (683)
		C	0	0.00 (0)	1	16.63 (422)	2	16.63 (422)	3	16.63 (422)	4	16.63 (422)	5	16.63 (422)
		D	6	3.88 (98)	9	3.88 (98)	12	3.88 (98)	15	3.88 (98)	18	3.88 (98)	21	3.88 (98)
		Weight, Lbs. (kg)	8.90 (4)		12.20 (5.5)		15.60 (7.1)		18.90 (8.6)		22.30 (10.1)		29.00 (13.2)	
	4	A	4	7.88 (200)	4	12.75 (324)	4	17.63 (448)	4	22.50 (572)	4	27.38 (695)	4	32.25 (819)
B*		2	31.25 (794)	2	31.25 (794)	2	31.25 (794)	2	31.25 (794)	2	31.25 (794)	3	31.25 (794)	
C		0	0.00 (0)	1	21.00 (533)	2	21.00 (533)	3	21.00 (533)	4	21.00 (533)	5	21.00 (533)	
D		8	3.88 (98)	12	3.88 (98)	8	3.88 (98)	20	3.88 (98)	25	3.88 (98)	28	3.88 (98)	
Weight, Lbs. (kg)		10.70 (4.8)		15.00 (6.8)		18.70 (8.5)		23.70 (10.7)		28.10 (12.7)		36.20 (16.4)		

*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar B = Support Rod C = Intermediate Rod D = Spacer Tube