


BOX CONNECTOR (Straight Threads)

A box connector creates a separable termination into a box. This connector has straight threads (NPS) and is supplied with a locknut. Sealing O-ring supplied by adding an EX suffix to the part number.

Nominal Size	Type	IPS Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
¾	SW	07A-SW-30	07C-SW-30	1.06 (27)	3 (76)	0.11	(.05)
1	SW	10A-SW-30	10C-SW-30	1.32 (34)	3 (76)	0.22	(.10)
1¼	SW	12A-SW-30	12C-SW-30	1.67 (42)	3 (76)	0.25	(.12)
1½	SW	15A-SW-30	15C-SW-30	1.91 (49)	3 (76)	0.29	(.13)
2	SW	20A-SW-30	20C-SW-30	2.40 (61)	5 (127)	0.85	(.39)
3	SW	30A-SW-30	30C-SW-30	3.52 (89)	5 (127)	1.28	(.58)
4	SW	40A-SW-30	40C-SW-30	4.47 (114)	5 (127)	2.09	(.95)
4	HW	40A-HW-30	40C-HW-30	4.52 (115)	5 (127)	2.09	(.95)
5	SW	50A-SW-30	50C-SW-30	5.54 (141)	5 (127)	2.75	(1.25)
5	MW	50A-MW-30	50C-MW-30	5.59 (142)	5 (127)	2.75	(1.25)
5	HW	50A-HW-30	50C-HW-30	5.63 (143)	5 (127)	2.75	(1.25)
6	SW	60A-SW-30	60C-SW-30	6.61 (168)	5 (127)	2.97	(1.35)
6	MW	60A-MW-30	60C-MW-30	6.66 (169)	5 (127)	2.97	(1.35)
6	HW	60A-HW-30	60C-HW-30	6.69 (170)	5 (127)	2.97	(1.35)

Nominal Size	Type	ID Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	SW	20B-SW-30	20D-SW-30	2.16 (55)	5 (127)	0.85	(.39)
2½	SW	25B-SW-30	25D-SW-30	2.66 (68)	5 (127)	0.94	(.43)
3	SW	30B-SW-30	30D-SW-30	3.16 (80)	5 (127)	1.28	(.58)
3½	SW	35B-SW-30	35D-SW-30	3.66 (93)	5 (127)	1.77	(.80)
4	SW	40B-SW-30	40D-SW-30	4.16 (106)	5 (127)	2.09	(.95)
4	HW	40B-HW-30	40D-HW-30	4.20 (107)	5 (127)	2.09	(.95)
4½	SW	45B-SW-30	45D-SW-30	4.66 (118)	5 (127)	2.40	(1.08)
4½	HW	45B-HW-30	45D-HW-30	4.70 (119)	5 (127)	2.40	(1.08)
5	SW	50B-SW-30	50D-SW-30	5.16 (131)	5 (127)	2.75	(1.25)
5	MW	50B-MW-30	50D-MW-30	5.20 (132)	5 (127)	2.75	(1.25)
5	HW	50B-HW-30	50D-HW-30	5.24 (133)	5 (127)	2.75	(1.25)
6	SW	60B-SW-30	60D-SW-30	6.16 (156)	5 (127)	2.97	(1.35)
6	MW	60B-MW-30	60D-MW-30	6.20 (157)	5 (127)	2.97	(1.35)
6	HW	60B-HW-30	60D-HW-30	6.24 (158)	5 (127)	2.97	(1.35)

Nominal Size	Type	Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	XW	20B-XW-30	20D-XW-30	2.520 (64)	5 (127)	0.85	(0.39)
2½	XW	25B-XW-30	25D-XW-30	3.025 (77)	5 (127)	0.94	(0.43)
3	XW	30B-XW-30	30D-XW-30	3.520 (89)	5 (127)	1.28	(0.58)
3½	XW	35B-XW-30	35D-XW-30	4.025 (102)	5 (127)	1.77	(0.80)
4	XW	40B-XW-30	40D-XW-30	4.520 (115)	7 (165)	2.09	(0.95)
5	XW	50B-XW-30	50D-XW-30	5.520 (140)	7 (165)	2.75	(1.25)
6	XW	60B-XW-30	60D-XW-30	6.520 (166)	7 (165)	2.97	(1.35)
8	XW	80A-XW-30	80C-XW-30	8.920 (227)	8 (203)	5.24	(2.37)



BOX CONNECTOR WITH GASKET (Straight Threads)

A box connector creates a separable termination into a box. This connector has straight threads (NPS) and is supplied with a locknut. Sealing O-ring supplied by adding an EX suffix to the part number.

Nominal Size	Type	IPS Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
¾	SW	07A-SW-30-G	07C-SW-30-G	1.06 (27)	3 (102)	0.08	(.04)
1	SW	10A-SW-30-G	10C-SW-30-G	1.32 (34)	3 (102)	0.08	(.04)
1¼	SW	12A-SW-30-G	12C-SW-30-G	1.67 (42)	3 (102)	0.15	(.07)
1½	SW	15A-SW-30-G	15C-SW-30-G	1.91 (49)	3 (102)	0.15	(.07)
2	SW	20A-SW-30-G	20C-SW-30-G	2.40 (61)	5 (127)	0.83	(0.38)
3	SW	30A-SW-30-G	30C-SW-30-G	3.52 (89)	5 (127)	1.10	(0.50)
4	SW	40A-SW-30-G	40C-SW-30-G	4.47 (114)	5 (127)	1.25	(0.57)
4	HW	40A-HW-30-G	40C-HW-30-G	4.52 (115)	5 (127)	1.25	(0.57)
5	SW	50A-SW-30-G	50C-SW-30-G	5.54 (141)	5 (127)	1.70	(0.77)
5	MW	50A-MW-30-G	50C-MW-30-G	5.59 (142)	5 (127)	1.65	(0.75)
5	HW	50A-HW-30-G	50C-HW-30-G	5.63 (143)	5 (127)	1.60	(0.73)
6	SW	60A-SW-30-G	60C-SW-30-G	6.61 (168)	5 (127)	2.20	(1.00)
6	MW	60A-MW-30-G	60C-MW-30-G	6.66 (169)	5 (127)	2.00	(0.91)
6	HW	60A-HW-30-G	60C-HW-30-G	6.69 (170)	5 (127)	1.80	(0.82)

Nominal Size	Type	ID Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	SW	20B-SW-30-G	20D-SW-30-G	2.16 (55)	5 (127)	0.65	(0.30)
2½	SW	25B-SW-30-G	25D-SW-30-G	2.66 (68)	5 (127)	0.80	(0.36)
3	SW	30B-SW-30-G	30D-SW-30-G	3.16 (80)	5 (127)	0.90	(0.41)
3½	SW	35B-SW-30-G	35D-SW-30-G	3.66 (93)	5 (127)	1.00	(0.45)
4	SW	40B-SW-30-G	40D-SW-30-G	4.16 (106)	5 (127)	1.40	(0.64)
4	HW	40B-HW-30-G	40D-HW-30-G	4.20 (107)	5 (127)	1.30	(0.59)
4½	SW	45B-SW-30-G	45D-SW-30-G	4.66 (118)	5 (127)	1.60	(0.73)
4½	HW	45B-HW-30-G	45D-HW-30-G	4.70 (119)	5 (127)	1.50	(0.68)
5	SW	50B-SW-30-G	50D-SW-30-G	5.16 (131)	5 (127)	1.60	(0.73)
5	MW	50B-MW-30-G	50D-MW-30-G	5.20 (132)	5 (127)	1.40	(0.64)
5	HW	50B-HW-30-G	50D-HW-30-G	5.24 (133)	5 (127)	1.28	(0.58)
6	SW	60B-SW-30-G	60D-SW-30-G	6.16 (156)	5 (127)	2.30	(1.04)
6	MW	60A-MW-30-G	60D-MW-30-G	6.20 (157)	5 (127)	2.10	(0.95)
6	HW	60B-HW-30-G	60D-HW-30-G	6.24 (158)	5 (127)	1.90	(0.86)