

BRIDGE HANGERS, 3.5" ID, SW, FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

	Part	Number of Ducts Wide											
		1		2		3		4		5		6	
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)
1	A	2	8.00 (203)	2	13.00 (330)	2	18.00 (457)	2	23.00 (584)	2	28.00 (711)	2	33.00 (838)
	B*	2	18.75 (476)	2	18.75 (476)	2	18.75 (476)	2	18.75 (476)	2	18.75 (476)	3	18.75 (476)
	C	0	0.00 (0)	1	8.50 (216)	2	8.50 (216)	3	8.50 (216)	4	8.50 (216)	4	8.50 (216)
	D	2	4.00 (102)	3	4.00 (102)	4	4.00 (102)	5	4.00 (102)	6	4.00 (102)	7	4.00 (102)
	Weight, Lbs. (kg)	6.00 (2.7)		7.80 (3.6)		9.70 (4.4)		11.50 (5.2)		13.40 (6.1)		16.50 (7.5)	
2	A	3	8.00 (203)	3	13.00 (330)	3	18.00 (457)	3	23.00 (584)	3	28.00 (711)	3	33.00 (838)
	B*	2	23.25 (591)	2	23.25 (591)	2	23.25 (591)	2	23.25 (591)	2	23.25 (591)	3	23.25 (591)
	C	0	0.00 (0)	1	13.00 (330)	2	13.00 (330)	3	13.00 (330)	4	13.00 (330)	5	13.00 (330)
	D	4	4.00 (102)	6	4.00 (102)	8	4.00 (102)	10	4.00 (102)	12	4.00 (102)	14	4.00 (102)
	Weight, Lbs. (kg)	7.80 (3.6)		10.70 (4.8)		13.50 (6.1)		16.40 (7.4)		19.20 (8.7)		25.00 (11.3)	
3	A	3	8.00 (203)	3	13.00 (330)	3	18.00 (457)	3	23.00 (584)	3	28.00 (711)	3	33.00 (838)
	B*	2	27.25 (692)	2	27.25 (692)	2	27.25 (692)	2	27.25 (692)	2	27.25 (692)	3	27.25 (692)
	C	0	0.00 (0)	1	17.00 (432)	2	17.00 (432)	3	17.00 (432)	4	17.00 (432)	5	17.00 (432)
	D	6	4.00 (102)	9	4.00 (102)	12	4.00 (102)	15	4.00 (102)	18	4.00 (102)	21	4.00 (102)
	Weight, Lbs. (kg)	9.00 (4.1)		12.40 (5.6)		15.90 (7.2)		19.30 (8.8)		22.80 (10.3)		29.60 (13.4)	
4	A	4	8.00 (203)	4	13.00 (330)	4	18.00 (457)	4	23.00 (584)	4	28.00 (711)	4	33.00 (838)
	B*	2	31.75 (806)	2	31.75 (806)	2	31.75 (806)	2	31.75 (806)	2	31.75 (806)	3	31.75 (806)
	C	0	0.00 (0)	1	21.50 (546)	2	21.50 (546)	3	21.50 (546)	4	21.50 (546)	5	21.50 (546)
	D	8	4.00 (102)	12	4.00 (102)	8	4.00 (102)	20	4.00 (102)	25	4.00 (102)	28	4.00 (102)
	Weight, Lbs. (kg)	10.90 (4.9)		15.30 (6.9)		19.00 (8.6)		24.20 (11)		28.70 (13)		37.00 (16.8)	

*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar B = Support Rod C = Intermediate Rod D = Spacer Tube

BRIDGE HANGERS, 4" ID, SW & HW, FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

	Part	Number of Ducts Wide											
		1		2		3		4		5		6	
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)
1	A	2	8.50 (216)	2	14.00 (356)	2	19.50 (495)	2	25.00 (635)	2	30.50 (775)	2	36.00 (914)
	B*	2	19.25 (489)	2	19.25 (489)	2	19.25 (489)	2	19.25 (489)	2	19.25 (489)	3	19.25 (489)
	C	0	0.00 (0)	1	9.00 (229)	2	9.00 (229)	3	9.00 (229)	4	9.00 (229)	4	9.00 (229)
	D	2	4.50 (114)	3	4.50 (114)	4	4.50 (114)	5	4.50 (114)	6	4.50 (114)	7	4.50 (114)
	Weight, Lbs. (kg)	6.20 (2.8)		8.20 (3.7)		10.20 (4.6)		12.20 (5.5)		14.20 (6.4)		17.40 (7.9)	
2	A	3	8.50 (216)	3	14.00 (356)	3	19.50 (495)	3	25.00 (635)	3	30.50 (775)	3	36.00 (914)
	B*	2	24.25 (616)	2	24.25 (616)	2	24.25 (616)	2	24.25 (616)	2	24.25 (616)	3	24.25 (616)
	C	0	0.00 (0)	1	14.00 (356)	2	14.00 (356)	3	14.00 (356)	4	14.00 (356)	5	14.00 (356)
	D	4	4.50 (114)	6	4.50 (114)	8	4.50 (114)	10	4.50 (114)	12	4.50 (114)	14	4.50 (114)
	Weight, Lbs. (kg)	8.20 (3.7)		11.30 (5.1)		14.40 (6.5)		17.50 (8)		20.60 (9.4)		26.80 (12.1)	
3	A	3	8.50 (216)	3	14.00 (356)	3	19.50 (495)	3	25.00 (635)	3	30.50 (775)	3	36.00 (914)
	B*	2	28.75 (730)	2	28.75 (730)	2	28.75 (730)	2	28.75 (730)	2	28.75 (730)	3	28.75 (730)
	C	0	0.00 (0)	1	18.50 (470)	2	18.50 (470)	3	18.50 (470)	4	18.50 (470)	5	18.50 (470)
	D	6	4.50 (114)	9	4.50 (114)	12	4.50 (114)	15	4.50 (114)	18	4.50 (114)	21	4.50 (114)
	Weight, Lbs. (kg)	9.60 (4.3)		13.30 (6)		17.10 (7.7)		20.80 (9.5)		24.60 (11.2)		32.00 (14.5)	
4	A	4	8.50 (216)	4	14.00 (356)	4	19.50 (495)	4	25.00 (635)	4	30.50 (775)	4	36.00 (914)
	B*	2	33.75 (857)	2	33.75 (857)	2	33.75 (857)	2	33.75 (857)	2	33.75 (857)	3	33.75 (857)
	C	0	0.00 (0)	1	23.50 (597)	2	23.50 (597)	3	23.50 (597)	4	23.50 (597)	5	23.50 (597)
	D	8	4.50 (114)	12	4.50 (114)	8	4.50 (114)	20	4.50 (114)	25	4.50 (114)	28	4.50 (114)
	Weight, Lbs. (kg)	11.60 (5.3)		16.50 (7.5)		20.60 (9.3)		26.20 (11.9)		31.20 (14.1)		40.20 (18.2)	

*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar B = Support Rod C = Intermediate Rod D = Spacer Tube