


MALE ADAPTER (Tapered Threads)

Male adapters with tapered threads (NPT) are generally used for joining to female threads of rigid steel, Myers type hubs or terminating into precast iron boxes with female thread entrances.

Nominal Size	Type	IPS Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
¾	SW	07A-SW-33	07C-SW-33	1.06 (27)	3 (76)	0.08	(.04)
1	SW	10A-SW-33	10C-SW-33	1.32 (34)	3 (76)	0.08	(.04)
1¼	SW	12A-SW-33	12C-SW-33	1.67 (42)	3 (76)	0.15	(.07)
1½	SW	15A-SW-33	15C-SW-33	1.91 (49)	3 (76)	0.15	(.07)
2	SW	20A-SW-33	20C-SW-33	2.40 (61)	5 (127)	0.44	(.20)
3	SW	30A-SW-33	30C-SW-33	3.52 (89)	5 (127)	0.64	(.29)
4	SW	40A-SW-33	40C-SW-33	4.47 (114)	5 (127)	0.93	(.42)
4	HW	40A-HW-33	40C-HW-33	4.52 (115)	5 (127)	0.97	(.44)
5	SW	50A-SW-33	50C-SW-33	5.54 (141)	5 (127)	1.45	(.66)
5	MW	50A-MW-33	50C-MW-33	5.59 (142)	5 (127)	1.30	(.59)
5	HW	50A-HW-33	50C-HW-33	5.63 (143)	5 (127)	1.15	(.52)
6	SW	60A-SW-33	60C-SW-33	6.61 (168)	5 (127)	2.00	(.91)
6	MW	60A-MW-33	60C-MW-33	6.66 (169)	5 (127)	1.70	(.77)
6	HW	60A-HW-33	60C-HW-33	6.69 (170)	5 (127)	1.40	(.64)

Nominal Size	Type	ID Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	SW	20B-SW-33	20D-SW-33	2.16 (55)	5 (127)	0.43	(.20)
2½	SW	25B-SW-33	25D-SW-33	2.66 (68)	5 (127)	0.62	(.28)
3	SW	30B-SW-33	30D-SW-33	3.16 (80)	5 (127)	0.76	(.35)
3½	SW	35B-SW-33	35D-SW-33	3.66 (93)	5 (127)	0.86	(.39)
4	SW	40B-SW-33	40D-SW-33	4.16 (106)	5 (127)	1.02	(.46)
4	HW	40B-HW-33	40D-HW-33	4.20 (107)	5 (127)	0.95	(.43)
4½	SW	45B-SW-33	45D-SW-33	4.66 (118)	5 (127)	1.22	(.55)
4½	HW	45B-HW-33	45D-HW-33	4.70 (119)	5 (127)	1.15	(.52)
5	SW	50B-SW-33	50D-SW-33	5.16 (131)	5 (127)	1.53	(.70)
5	MW	50B-MW-33	50D-MW-33	5.20 (132)	5 (127)	1.30	(.59)
5	HW	50B-HW-33	50D-HW-33	5.24 (133)	5 (127)	1.18	(.54)
6	SW	60B-SW-33	60D-SW-33	6.16 (156)	5 (127)	2.08	(.94)
6	MW	60B-MW-33	60D-MW-33	6.20 (157)	5 (127)	1.40	(.64)
6	HW	60B-HW-33	60D-HW-33	6.24 (158)	5 (127)	1.30	(.59)

Nominal Size	Type	Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	XW	20B-XW-33	20D-XW-33	2.520 (64)	5 (127)	0.69	(0.31)
2½	XW	25B-XW-33	25D-XW-33	3.025 (77)	5 (127)	0.85	(0.38)
3	XW	30B-XW-33	30D-XW-33	3.520 (89)	5 (127)	1.00	(0.45)
3½	XW	35B-XW-33	35D-XW-33	4.025 (102)	5 (127)	1.28	(0.58)
4	XW	40B-XW-33	40D-XW-33	4.520 (115)	7 (178)	1.56	(0.71)
5	XW	50B-XW-33	50D-XW-33	5.520 (140)	7 (178)	2.08	(0.94)
6	XW	60B-XW-33	60D-XW-33	6.520 (166)	7 (178)	2.47	(1.12)



MALE ADAPTER WITH GASKET (Tapered Threads)

Male adapters with tapered threads (NPT) are generally used for joining to female threads of rigid steel, Myers type hubs or terminating into precast iron boxes with female thread entrances.

Nominal Size	Type	IPS Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
¾	SW	07A-SW-33-G	07C-SW-33-G	1.06 (27)	3 (102)	0.08	(0.04)
1	SW	10A-SW-33-G	10C-SW-33-G	1.32 (34)	3 (102)	0.08	(0.04)
1¼	SW	12A-SW-33-G	12C-SW-33-G	1.67 (42)	3 (102)	0.15	(0.07)
1½	SW	15A-SW-33-G	15C-SW-33-G	1.91 (49)	3 (102)	0.15	(0.07)
2	SW	20A-SW-33-G	20C-SW-33-G	2.40 (61)	5 (127)	0.83	(0.38)
3	SW	30A-SW-33-G	30C-SW-33-G	3.52 (89)	5 (127)	1.10	(0.50)
4	SW	40A-SW-33-G	40C-SW-33-G	4.47 (114)	5 (127)	1.35	(0.61)
4	HW	40A-HW-33-G	40C-HW-33-G	4.52 (115)	5 (127)	1.25	(0.57)
5	SW	50A-SW-33-G	50C-SW-33-G	5.54 (141)	5 (127)	1.70	(0.77)
5	MW	50A-MW-33-G	50C-MW-33-G	5.59 (142)	5 (127)	1.65	(0.75)
5	HW	50A-HW-33-G	50C-HW-33-G	5.63 (143)	5 (127)	1.68	(0.76)
6	SW	60A-SW-33-G	60C-SW-33-G	6.61 (168)	5 (127)	2.20	(1.00)
6	MW	60A-MW-33-G	60C-MW-33-G	6.66 (169)	5 (127)	2.00	(0.91)
6	HW	60A-HW-33-G	60C-HW-33-G	6.69 (170)	5 (127)	1.80	(0.82)

Nominal Size	Type	ID Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	SW	20B-SW-33-G	20D-SW-33-G	2.16 (55)	5 (127)	0.65	(0.30)
2½	SW	25B-SW-33-G	25D-SW-33-G	2.66 (68)	5 (127)	0.80	(0.36)
3	SW	30B-SW-33-G	30D-SW-33-G	3.16 (80)	5 (127)	0.90	(0.41)
3½	SW	35B-SW-33-G	35D-SW-33-G	3.66 (93)	5 (127)	1.00	(0.45)
4	SW	40B-SW-33-G	40D-SW-33-G	4.16 (106)	5 (127)	1.40	(0.64)
4	HW	40B-HW-33-G	40D-HW-33-G	4.20 (107)	5 (127)	1.30	(0.59)
4½	SW	45B-SW-33-G	45D-SW-33-G	4.66 (118)	5 (127)	1.60	(0.73)
4½	HW	45B-HW-33-G	45D-HW-33-G	4.70 (119)	5 (127)	1.50	(0.68)
5	SW	50B-SW-33-G	50D-SW-33-G	5.16 (131)	5 (127)	1.60	(0.73)
5	MW	50B-MW-33-G	50D-MW-33-G	5.20 (132)	5 (127)	1.40	(0.64)
5	HW	50B-HW-33-G	50D-HW-33-G	5.24 (133)	5 (127)	1.28	(0.58)
6	SW	60B-SW-33-G	60D-SW-33-G	6.16 (156)	5 (127)	2.30	(1.04)
6	MW	60B-MW-33-G	60D-MW-33-G	6.20 (157)	5 (127)	2.10	(0.95)
6	HW	60B-HW-33-G	60D-HW-33-G	6.24 (158)	5 (127)	1.90	(0.86)