

BRIDGE HANGERS, 4" IPS, SW & HW & 4" ID, XW FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

Part		Number of Ducts Wide											
		1		2		3		4		5		6	
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)
1	A	2	8.88 (225)	2	14.75 (375)	2	20.63 (524)	2	26.50 (673)	2	32.38 (822)	2	38.25 (972)
	B*	2	19.63 (498)	2	19.63 (498)	2	19.63 (498)	2	19.63 (498)	2	19.63 (498)	3	19.63 (498)
	C	0	0.00 (0)	1	9.38 (238)	2	9.38 (238)	3	9.38 (238)	4	9.38 (238)	4	9.38 (238)
	D	2	4.88 (124)	3	4.88 (124)	4	4.88 (124)	5	4.88 (124)	6	4.88 (124)	7	4.88 (124)
	Weight, Lbs. (kg)	6.40 (2.9)		8.50 (3.8)		10.60 (4.8)		12.70 (5.7)		14.80 (6.7)		18.10 (8.2)	
2	A	3	8.88 (225)	3	14.75 (375)	3	20.63 (524)	3	26.50 (673)	3	32.38 (822)	3	38.25 (972)
	B*	2	25.00 (635)	2	25.00 (635)	2	25.00 (635)	2	25.00 (635)	2	25.00 (635)	3	25.00 (635)
	C	0	0.00 (0)	1	14.75 (375)	2	14.75 (375)	3	14.75 (375)	4	14.75 (375)	5	14.75 (375)
	D	4	4.88 (124)	6	4.88 (124)	8	4.88 (124)	10	4.88 (124)	12	4.88 (124)	14	4.88 (124)
	Weight, Lbs. (kg)	8.50 (3.9)		11.80 (5.4)		15.10 (6.9)		18.40 (8.3)		21.70 (9.8)		28.10 (12.7)	
3	A	3	8.88 (225)	3	14.75 (375)	3	20.63 (524)	3	26.50 (673)	3	32.38 (822)	3	38.25 (972)
	B*	2	29.88 (759)	2	29.88 (759)	2	29.88 (759)	2	29.88 (759)	2	29.88 (759)	3	29.88 (759)
	C	0	0.00 (0)	1	19.63 (498)	2	19.63 (498)	3	19.63 (498)	4	19.63 (498)	5	19.63 (498)
	D	6	4.88 (124)	9	4.88 (124)	12	4.88 (124)	15	4.88 (124)	18	4.88 (124)	21	4.88 (124)
	Weight, Lbs. (kg)	10.00 (4.5)		14.00 (6.3)		18.00 (8.2)		22.00 (10)		26.00 (11.8)		33.70 (15.3)	
4	A	4	8.88 (225)	4	14.75 (375)	4	20.63 (524)	4	26.50 (673)	4	32.38 (822)	4	38.25 (972)
	B*	2	35.25 (895)	2	35.25 (895)	2	35.25 (895)	2	35.25 (895)	2	35.25 (895)	3	35.25 (895)
	C	0	0.00 (0)	1	25.00 (635)	2	25.00 (635)	3	25.00 (635)	4	25.00 (635)	5	25.00 (635)
	D	8	4.88 (124)	12	4.88 (124)	8	4.88 (124)	20	4.88 (124)	25	4.88 (124)	28	4.88 (124)
	Weight, Lbs. (kg)	12.10 (5.5)		17.30 (7.9)		21.70 (9.8)		27.70 (12.6)		33.00 (15)		42.50 (19.3)	

*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar B = Support Rod C = Intermediate Rod D = Spacer Tube

BRIDGE HANGERS, 4.5" ID, SW & HW FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

Part		Number of Ducts Wide											
		1		2		3		4		5		6	
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)
1	A	2	9.00 (229)	2	15.00 (381)	2	21.00 (533)	2	27.00 (686)	2	33.00 (838)	2	39.00 (991)
	B*	2	19.75 (502)	2	19.75 (502)	2	19.75 (502)	2	19.75 (502)	2	19.75 (502)	3	19.75 (502)
	C	0	0.00 (0)	1	9.50 (241)	2	9.50 (241)	3	9.50 (241)	4	9.50 (241)	4	9.50 (241)
	D	2	5.00 (127)	3	5.00 (127)	4	5.00 (127)	5	5.00 (127)	6	5.00 (127)	7	5.00 (127)
	Weight, Lbs. (kg)	6.40 (2.9)		8.60 (3.9)		10.70 (4.8)		12.80 (5.8)		15.00 (6.8)		18.40 (8.3)	
2	A	3	9.00 (229)	3	15.00 (381)	3	21.00 (533)	3	27.00 (686)	3	33.00 (838)	3	39.00 (991)
	B*	2	25.25 (641)	2	25.25 (641)	2	25.25 (641)	2	25.25 (641)	2	25.25 (641)	3	25.25 (641)
	C	0	0.00 (0)	1	15.00 (381)	2	15.00 (381)	3	15.00 (381)	4	15.00 (381)	5	15.00 (381)
	D	4	5.00 (127)	6	5.00 (127)	8	5.00 (127)	10	5.00 (127)	12	5.00 (127)	14	5.00 (127)
	Weight, Lbs. (kg)	8.60 (3.9)		12.00 (5.4)		15.30 (7)		18.70 (8.5)		22.00 (10)		28.60 (13)	
3	A	3	9.00 (229)	3	15.00 (381)	3	21.00 (533)	3	27.00 (686)	3	33.00 (838)	3	39.00 (991)
	B*	2	30.25 (768)	2	30.25 (768)	2	30.25 (768)	2	30.25 (768)	2	30.25 (768)	3	30.25 (768)
	C	0	0.00 (0)	1	20.00 (508)	2	20.00 (508)	3	20.00 (508)	4	20.00 (508)	5	20.00 (508)
	D	6	5.00 (127)	9	5.00 (127)	12	5.00 (127)	15	5.00 (127)	18	5.00 (127)	21	5.00 (127)
	Weight, Lbs. (kg)	10.10 (4.6)		14.20 (6.4)		18.30 (8.3)		22.40 (10.1)		26.40 (12)		34.30 (15.6)	
4	A	4	9.00 (229)	4	15.00 (381)	4	21.00 (533)	4	27.00 (686)	4	33.00 (838)	4	39.00 (991)
	B*	2	35.75 (908)	2	35.75 (908)	2	35.75 (908)	2	35.75 (908)	2	35.75 (908)	3	35.75 (908)
	C	0	0.00 (0)	1	25.50 (648)	2	25.50 (648)	3	25.50 (648)	4	25.50 (648)	5	25.50 (648)
	D	8	5.00 (127)	12	5.00 (127)	8	5.00 (127)	20	5.00 (127)	25	5.00 (127)	28	5.00 (127)
	Weight, Lbs. (kg)	12.30 (5.6)		17.60 (8)		22.10 (10)		28.20 (12.8)		33.60 (15.3)		43.30 (19.6)	

*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar B = Support Rod C = Intermediate Rod D = Spacer Tube