


### SPECIAL ADAPTER FOR PVC COATED FITTINGS (Male Terminal Adapter)

This terminal adapter has tapered threads and a straight shoulder so it can fit under the PVC sleeve of a PVC coated steel fitting.

Nominal Size	Type	IPS Item No.		D	L	L1	Weight	
		Belowground	Aboveground				lbs	kg
3/4	SW	07A-SW-24	07C-SW-24	1.06 (27)	3 3/4 (95)	3/4	0.10	(3.00)
1	SW	10A-SW-24	10C-SW-24	1.32 (34)	4 (102)	1	0.13	(3.00)
1 1/4	SW	12A-SW-24	12C-SW-24	1.67 (42)	4 1/4 (108)	1 1/4	0.18	(5.00)
1 1/2	SW	15A-SW-24	15C-SW-24	1.91 (49)	4 1/2 (114)	1 1/2	0.18	(5.00)
2	SW	20A-SW-24	20C-SW-24	2.40 (61)	7 (178)	2	0.60	(15.00)
3	SW	30A-SW-24	30C-SW-24	3.52 (89)	7 (178)	2	0.80	(20.00)
4	SW	40A-SW-24	40C-SW-24	4.47 (114)	7 (178)	2	1.20	(30.00)
4	HW	40A-HW-24	40C-HW-24	4.52 (115)	7 (178)	2	1.30	(33.00)
5	SW	50A-SW-24	50C-SW-24	5.54 (141)	7 (178)	2	1.90	(48.00)
5	MW	50A-MW-24	50C-MW-24	5.59 (142)	7 (178)	2	1.70	(43.00)
5	HW	50A-HW-24	50C-HW-24	5.63 (143)	7 (178)	2	1.50	(38.00)
6	SW	60A-SW-24	60C-SW-24	6.61 (168)	7 (178)	2	2.60	(66.00)
6	MW	60A-MW-24	60C-MW-24	6.66 (169)	7 (178)	2	2.20	(56.00)
6	HW	60A-HW-24	60C-HW-24	6.69 (170)	7 (178)	2	1.80	(46.00)

Nominal Size	Type	Item No.		D	L	L1	Weight	
		Belowground	Aboveground				lbs	kg
2	XW	20B-XW-24	20D-XW-24	2.520 (64)	7 (178)	2 (51)	0.69	(0.31)
2 1/2	XW	25B-XW-24	25D-XW-24	3.025 (77)	7 (178)	2 (51)	1.20	(0.45)
3	XW	30B-XW-24	30D-XW-24	3.520 (89)	7 (178)	2 (51)	1.00	(0.45)
3 1/2	XW	35B-XW-24	35D-XW-24	4.025 (102)	7 (178)	2 (51)	1.20	(0.54)
4	XW	40B-XW-24	40D-XW-24	4.520 (115)	7 (178)	2 (51)	1.56	(0.71)
5	XW	50B-XW-24	50D-XW-24	5.520 (140)	7 (178)	2 (51)	2.08	(0.94)
6	XW	60B-XW-24	60D-XW-24	6.520 (166)	7 (178)	2 (51)	2.47	(1.12)



### FEMALE TERMINAL ADAPTER

This adapter is generally used for joining fiberglass conduit with galvanized rigid steel (GRS) conduit. It has the same threads as GRS conduit and can easily be attached to GRS conduit.

Nominal Size	Type	IPS Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
3/4	SW	07A-SW-32	07C-SW-32	1.06 (27)	3.0 (76)		0.07 (0.03)
1	SW	10A-SW-32	10C-SW-32	1.32 (34)	3.0 (76)		0.13 (0.06)
1 1/4	SW	12A-SW-32	12C-SW-32	1.67 (42)	3.0 (76)		0.18 (0.08)
1 1/2	SW	15A-SW-32	15C-SW-32	1.91 (49)	3.0 (76)		0.21 (0.10)
2	SW	20A-SW-32	20C-SW-32	2.40 (61)	5.0 (127)		0.47 (0.21)
3	SW	30A-SW-32	30C-SW-32	3.52 (89)	5.0 (127)		0.80 (0.36)
4	SW	40A-SW-32	40C-SW-32	4.47 (114)	5.0 (127)		1.05 (0.48)
4	HW	40A-HW-32	40C-HW-32	4.52 (115)	5.0 (127)		1.00 (0.45)
5	SW	50A-SW-32	50C-SW-32	5.54 (141)	5.0 (127)		1.10 (0.50)
5	MW	50A-MW-32	50C-MW-32	5.59 (142)	5.0 (127)		1.05 (0.48)
5	HW	50A-HW-32	50C-HW-32	5.63 (143)	5.0 (127)		1.00 (0.45)
6	SW	60A-SW-32	60C-SW-32	6.61 (168)	5.0 (127)		1.15 (0.52)
6	MW	60A-MW-32	60C-MW-32	6.66 (169)	5.0 (127)		1.10 (0.50)
6	HW	60A-HW-32	60C-HW-32	6.69 (170)	5.0 (127)		1.05 (0.48)

Nominal Size	Type	ID Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	SW	20B-SW-32	20D-SW-32	2.16 (55)	5 (127)		0.75 (0.34)
2 1/2	SW	25B-SW-32	25D-SW-32	2.66 (55)	5 (127)		1.00 (0.45)
3	SW	30B-SW-32	30D-SW-32	3.16 (80)	5 (127)		1.08 (0.49)
3 1/2	SW	35B-SW-32	35D-SW-32	3.66 (93)	5 (127)		1.18 (0.54)
4	SW	40B-SW-32	40D-SW-32	4.16 (106)	5 (127)		1.25 (0.57)
4	HW	40B-HW-32	40D-HW-32	4.20 (107)	5 (127)		1.08 (0.49)
4 1/2	SW	45B-SW-32	45D-SW-32	4.66 (118)	5 (127)		1.50 (0.68)
4 1/2	HW	45B-HW-32	45D-HW-32	4.70 (119)	5 (127)		1.40 (0.64)
5	SW	50B-SW-32	50D-SW-32	5.16 (131)	5 (127)		1.90 (0.86)
5	MW	50B-MW-32	50D-MW-32	5.20 (132)	5 (127)		1.75 (0.80)
5	HW	50B-HW-32	50D-HW-32	5.24 (133)	5 (127)		1.65 (0.75)
6	SW	60B-SW-32	60D-SW-32	6.16 (156)	5 (127)		2.13 (0.97)
6	MW	60B-MW-32	60D-MW-32	6.20 (157)	5 (127)		2.00 (0.91)
6	HW	60B-HW-32	60D-HW-32	6.24 (158)	5 (127)		1.83 (0.83)

Nominal Size	Type	Item No.		D	L	Weight	
		Belowground	Aboveground			lbs	kg
2	XW	20B-XW-32	20D-XW-32	2.520 (64)	5 (127)		1.20 (0.55)
2 1/2	XW	25B-XW-32	25D-XW-32	3.025 (77)	5 (127)		0.85 (0.38)
3	XW	30B-XW-32	30D-XW-32	3.520 (89)	5 (127)		1.40 (0.64)
3 1/2	XW	35B-XW-32	35D-XW-32	4.025 (102)	5 (127)		1.28 (0.58)
4	XW	40B-XW-32	40D-XW-32	4.520 (115)	7 (178)		2.08 (0.94)
5	XW	50B-XW-32	50D-XW-32	5.520 (140)	7 (178)		2.60 (1.18)
6	XW	60B-XW-32	60D-XW-32	6.520 (166)	7 (178)		3.51 (1.59)