

## BRIDGE HANGERS, 6" ID, SW, MW & HW FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

		Number of Ducts Wide											
		1		2		3		4		5		6	
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)
1	A	2	10.50 (267)	2	18.00 (457)	2	25.50 (648)	2	33.00 (838)	2	40.50 (1029)	2	48.00 (1219)
	B*	2	21.25 (540)	2	21.25 (540)	2	21.25 (540)	2	21.25 (540)	2	21.25 (540)	3	21.25 (540)
	C	0	0.00 (0)	1	11.00 (279)	2	11.00 (279)	3	11.00 (279)	4	11.00 (279)	4	11.00 (279)
	D	2	6.50 (165)	3	6.50 (165)	4	6.50 (165)	5	6.50 (165)	6	6.50 (165)	7	6.50 (165)
Weight, Lbs. (kg)		7.10 (3.2)		9.60 (4.4)		12.20 (5.5)		14.80 (6.7)		17.30 (7.9)		21.20 (9.6)	
2	A	3	10.50 (267)	3	18.00 (457)	3	25.50 (648)	3	33.00 (838)	3	40.50 (1029)	3	48.00 (1219)
	B*	2	28.25 (718)	2	28.25 (718)	2	28.25 (718)	2	28.25 (718)	2	28.25 (718)	3	28.25 (718)
	C	0	0.00 (0)	1	18.00 (457)	2	18.00 (457)	3	18.00 (457)	4	18.00 (457)	5	18.00 (457)
	D	4	6.50 (165)	6	6.50 (165)	8	6.50 (165)	10	6.50 (165)	12	6.50 (165)	14	6.50 (165)
Weight, Lbs. (kg)		9.80 (4.5)		13.90 (6.3)		18.00 (8.2)		22.20 (10)		26.30 (11.9)		33.90 (15.4)	
3	A	3	10.50 (267)	3	18.00 (457)	3	25.50 (648)	3	33.00 (838)	3	40.50 (1029)	3	48.00 (1219)
	B*	2	34.75 (883)	2	34.75 (883)	2	34.75 (883)	2	34.75 (883)	2	34.75 (883)	3	34.75 (883)
	C	0	0.00 (0)	1	24.50 (622)	2	24.50 (622)	3	24.50 (622)	4	24.50 (622)	5	24.50 (622)
	D	6	6.50 (165)	9	6.50 (165)	12	6.50 (165)	15	6.50 (165)	18	6.50 (165)	21	6.50 (165)
Weight, Lbs. (kg)		11.70 (5.3)		16.80 (7.6)		21.90 (9.9)		26.90 (12.2)		32.00 (14.5)		41.40 (18.8)	
4	A	4	10.50 (267)	4	18.00 (457)	4	25.50 (648)	4	33.00 (838)	4	40.50 (1029)	4	48.00 (1219)
	B*	2	41.75 (1060)	2	41.75 (1060)	2	41.75 (1060)	2	41.75 (1060)	2	41.75 (1060)	3	41.75 (1060)
	C	0	0.00 (0)	1	31.50 (800)	2	31.50 (800)	3	31.50 (800)	4	31.50 (800)	5	31.50 (800)
	D	8	6.50 (165)	12	6.50 (165)	8	6.50 (165)	20	6.50 (165)	25	6.50 (165)	28	6.50 (165)
Weight, Lbs. (kg)		14.50 (6.6)		21.10 (9.6)		26.60 (12.1)		34.30 (15.6)		41.00 (18.6)		52.70 (23.9)	

\*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar      B = Support Rod      C = Intermediate Rod      D = Spacer Tube

## BRIDGE HANGERS, 6" IPS, SW, MW & HW & 6" ID, XW FIBERGLASS CONDUIT

Intermediate Type (Note: Detailed drawings & dimensional layouts are available to download from our web site.)

		Number of Ducts Wide											
		1		2		3		4		5		6	
		No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)	No. Req'd	Length inch (mm)
1	A	2	10.88 (276)	2	18.75 (476)	2	26.63 (676)	2	34.50 (876)	2	42.38 (1076)	2	50.25 (1276)
	B*	2	21.63 (549)	2	21.63 (549)	2	21.63 (549)	2	21.63 (549)	2	21.63 (549)	3	21.63 (549)
	C	0	0.00 (0)	1	11.38 (289)	2	11.38 (289)	3	11.38 (289)	4	11.38 (289)	4	11.38 (289)
	D	2	6.88 (175)	3	6.88 (175)	4	6.88 (175)	5	6.88 (175)	6	6.88 (175)	7	6.88 (175)
Weight, Lbs. (kg)		7.20 (3.3)		9.90 (4.5)		12.60 (5.7)		15.20 (6.9)		17.90 (8.1)		21.90 (9.9)	
2	A	3	10.88 (276)	3	18.75 (476)	3	26.63 (676)	3	34.50 (876)	3	42.38 (1076)	3	50.25 (1276)
	B*	2	29.00 (737)	2	29.00 (737)	2	29.00 (737)	2	29.00 (737)	2	29.00 (737)	3	29.00 (737)
	C	0	0.00 (0)	1	18.75 (476)	2	18.75 (476)	3	18.75 (476)	4	18.75 (476)	5	18.75 (476)
	D	4	6.88 (175)	6	6.88 (175)	8	6.88 (175)	10	6.88 (175)	12	6.88 (175)	14	6.88 (175)
Weight, Lbs. (kg)		10.10 (4.6)		14.40 (6.5)		18.70 (8.5)		23.00 (10.4)		27.30 (12.4)		35.20 (16)	
3	A	3	10.88 (276)	3	18.75 (476)	3	26.63 (676)	3	34.50 (876)	3	42.38 (1076)	3	50.25 (1276)
	B*	2	35.88 (911)	2	35.88 (911)	2	35.88 (911)	2	35.88 (911)	2	35.88 (911)	3	35.88 (911)
	C	0	0.00 (0)	1	25.63 (651)	2	25.63 (651)	3	25.63 (651)	4	25.63 (651)	5	25.63 (651)
	D	6	6.88 (175)	9	6.88 (175)	12	6.88 (175)	15	6.88 (175)	18	6.88 (175)	21	6.88 (175)
Weight, Lbs. (kg)		12.10 (5.5)		17.50 (7.9)		22.80 (10.3)		28.10 (12.7)		33.40 (15.1)		43.10 (19.6)	
4	A	4	10.88 (276)	4	18.75 (476)	4	26.63 (676)	4	34.50 (876)	4	42.38 (1076)	4	50.25 (1276)
	B*	2	43.25 (1099)	2	43.25 (1099)	2	43.25 (1099)	2	43.25 (1099)	2	43.25 (1099)	3	43.25 (1099)
	C	0	0.00 (0)	1	33.00 (838)	2	33.00 (838)	3	33.00 (838)	4	33.00 (838)	5	33.00 (838)
	D	8	6.88 (175)	12	6.88 (175)	8	6.88 (175)	20	6.88 (175)	25	6.88 (175)	28	6.88 (175)
Weight, Lbs. (kg)		15.00 (6.8)		22.00 (10)		27.70 (12.6)		35.80 (16.3)		42.90 (19.5)		55.10 (25)	

\*These dimensions are based on the support rod being 12" lg [305] above the top horizontal cross member.

A = Horizontal Flatbar      B = Support Rod      C = Intermediate Rod      D = Spacer Tube