


## CONDUIT BODIES


All conduit bodies are manufactured by compression molding for ultimate strength. The conduit bodies are made from phenolic resin with high glass content and meet the same flame and smoke standards as the conduit itself. Each conduit body is supplied with a high performance rubber gasket to provide a water tight seal between the cover and conduit body. All hardware is stainless steel.



### TYPE C

Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07E-SW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10E-SW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12E-SW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15E-SW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20E-SW-C	13.375 (340)	4.000 (102)	3.040 (77)	1.812 (46)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25F-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30E-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40E-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)

Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	XW	07E-XW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.435 (36)	13.90 (228)	0.70 (0.32)
1	XW	10E-XW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.700 (43)	13.90 (228)	0.70 (0.32)
1¼	XW	12E-XW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	2.045 (52)	32.00 (524)	1.20 (0.54)
1½	XW	15E-XW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	2.285 (58)	32.00 (524)	1.10 (0.50)
2	XW	20F-XW-C	13.375 (340)	4.000 (102)	3.040 (77)	1.812 (46)	2.520 (64)	70.75 (1160)	2.50 (1.13)
2½	XW	25F-XW-C	13.375 (340)	4.000 (102)	3.040 (77)	1.812 (46)	3.025 (77)	70.75 (1160)	2.50 (1.13)
3	XW	30F-XW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.520 (89)	425.00 (6964)	4.24 (1.92)
3½	XW	35F-XW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	4.025 (102)	425.00 (6964)	4.24 (1.92)
4	XW	40F-XW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	4.520 (115)	425.00 (6964)	4.24 (1.92)



### TYPE LB

Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	H <sub>2</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07E-SW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10E-SW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12E-SW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15E-SW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20E-SW-LB	11.250 (286)	4.000 (102)	3.040 (77)	1.812 (46)	6.687 (170)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30E-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40E-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	4.508 (114)	425.00 (6964)	4.24 (1.92)

Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	H <sub>2</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	XW	07E-XW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.435 (36)	13.90 (228)	0.70 (0.32)
1	XW	10E-XW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.700 (43)	13.90 (228)	0.70 (0.32)
1¼	XW	12E-XW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	2.045 (52)	32.00 (524)	1.20 (0.54)
1½	XW	15E-XW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	2.285 (58)	32.00 (524)	1.10 (0.50)
2	XW	20F-XW-LB	11.250 (286)	4.000 (102)	3.040 (77)	1.812 (46)	6.687 (170)	2.520 (64)	70.75 (1160)	2.50 (1.13)
2½	XW	25F-XW-LB	11.250 (286)	4.000 (102)	3.040 (77)	1.812 (46)	6.687 (170)	3.025 (77)	70.75 (1160)	2.50 (1.13)
3	XW	30F-XW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.520 (89)	425.00 (6964)	4.24 (1.92)
3½	XW	35F-XW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	4.025 (102)	425.00 (6964)	4.24 (1.92)
4	XW	40F-XW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	4.520 (115)	425.00 (6964)	4.24 (1.92)