


ELBOWS

Radii listed are available and larger radii can be supplied. Contact your local representative or Champion Fiberglass for additional information. All elbows are supplied with plain ends. For installations with other conduit systems, we offer an assortment of transition and termination fittings that can be installed on our elbows. Please see page 44 for a selection of elbows with PVC couplings.




11¼° X 12"

Nominal Size	Type	IPS Item No.		M	O-Tangent (min)	R - Radius (min)	Weight	
		Belowground	Aboveground				lbs	kg
¾	SW	07A-SW-50-P	07C-SW-50-P	1.05 (27)	6 (152)	12 (305)	0.20	(0.09)
1	SW	10A-SW-50-P	10C-SW-50-P	1.32 (33)	6 (152)	12 (305)	0.22	(0.10)
1¼	SW	12A-SW-50-P	12C-SW-50-P	1.66 (42)	6 (152)	12 (305)	0.27	(0.12)
1½	SW	15A-SW-50-P	15C-SW-50-P	1.90 (48)	6 (152)	12 (305)	0.39	(0.18)
2	SW	20A-SW-50-P	20C-SW-50-P	2.37 (60)	6 (152)	12 (305)	0.44	(0.20)
2½	SW	25A-SW-50-P	25C-SW-50-P	2.88 (73)	6 (152)	12 (305)	0.54	(0.25)

Nominal Size	Type	ID Item No.		M	O-Tangent (min)	R - Radius (min)	Weight	
		Belowground	Aboveground				lbs	kg
2	SW	20B-SW-50-P	20D-SW-50-P	2.14 (54)	6 (152)	12 (305)	0.40	(0.18)
2½	SW	25B-SW-50-P	25D-SW-50-P	2.64 (67)	6 (152)	12 (305)	0.49	(0.22)

Nominal Size	Type	Item No.		M	O-Tangent (min)	R - Radius (min)	Weight	
		Belowground	Aboveground				lbs	kg
2	XW	20B-XW-50-P	20D-XW-50-P	2.50 (63)	6 (152)	12 (305)	1.47	(0.67)
2½	XW	25B-XW-50-P	25D-XW-50-P	3.00 (76)	6 (152)	12 (305)	1.80	(0.82)
3	XW	30B-XW-50-P	30D-XW-50-P	4.00 (102)	6 (152)	12 (305)	2.45	(1.11)



11¼° X 24"

Nominal Size	Type	IPS Item No.		M	O-Tangent (min)	R - Radius (min)	Weight	
		Belowground	Aboveground				lbs	kg
¾	SW	07A-SW-51-P	07C-SW-51-P	1.05 (27)	6 (152)	24 (610)	0.24	(0.11)
1	SW	10A-SW-51-P	10C-SW-51-P	1.32 (33)	6 (152)	24 (610)	0.27	(0.12)
1¼	SW	12A-SW-51-P	12C-SW-51-P	1.66 (42)	6 (152)	24 (610)	0.33	(0.15)
1½	SW	15A-SW-51-P	15C-SW-51-P	1.90 (48)	6 (152)	24 (610)	0.47	(0.21)
2	SW	20A-SW-51-P	20C-SW-51-P	2.37 (60)	6 (152)	24 (610)	0.54	(0.25)
2½	SW	25A-SW-51-P	25C-SW-51-P	2.88 (73)	6 (152)	24 (610)	0.65	(0.30)
3	SW	30A-SW-51-P	30C-SW-51-P	3.50 (89)	6 (152)	24 (610)	0.85	(0.38)
4	SW	40A-SW-51-P	40C-SW-51-P	4.46 (113)	6 (152)	24 (610)	1.02	(0.46)
4	HW	40A-HW-51-P	40C-HW-51-P	4.51 (114)	6 (152)	24 (610)	1.37	(0.61)

Nominal Size	Type	ID Item No.		M	O-Tangent (min)	R - Radius (min)	Weight	
		Belowground	Aboveground				lbs	kg
2	SW	20B-SW-51-P	20D-SW-51-P	2.14 (54)	6 (152)	24 (610)	0.48	(0.22)
2½	SW	25B-SW-51-P	25D-SW-51-P	2.64 (67)	6 (152)	24 (610)	0.60	(0.27)
3	SW	30B-SW-51-P	30D-SW-51-P	3.14 (80)	6 (152)	24 (610)	0.68	(0.25)
3½	SW	35B-SW-51-P	35D-SW-51-P	3.64 (92)	6 (152)	24 (610)	0.86	(0.39)
4	SW	40B-SW-51-P	40D-SW-51-P	4.14 (105)	6 (152)	24 (610)	0.98	(0.45)
4	HW	40B-HW-51-P	40D-HW-51-P	4.19 (106)	6 (152)	24 (610)	1.48	(0.67)

Nominal Size	Type	Item No.		M	O-Tangent (min)	R - Radius (min)	Weight	
		Belowground	Aboveground				lbs	kg
2	XW	20B-XW-51-P	20D-XW-51-P	2.50 (63)	6 (152)	24 (610)	1.79	(0.81)
2½	XW	25B-XW-51-P	25D-XW-51-P	3.00 (76)	6 (152)	24 (610)	2.19	(0.99)
3	XW	30B-XW-51-P	30D-XW-51-P	3.50 (89)	6 (152)	24 (610)	2.58	(1.17)
3½	XW	35B-XW-51-P	35D-XW-51-P	4.00 (102)	6 (152)	24 (610)	2.98	(1.35)
4	XW	40B-XW-51-P	40D-XW-51-P	4.50 (114)	6 (152)	24 (610)	3.38	(1.53)