


## CONDUIT BODIES


All conduit bodies are manufactured by compression molding for ultimate strength. The conduit bodies are made of vinyl ester resin with high glass content, flame retardant per UL 2515 and CSA C22.2 No. 2515 and halogen free. Each conduit body is supplied with a high performance rubber gasket to provide a water tight seal between the cover and conduit body. Provided hardware is stainless steel.

### TYPE C




Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07C-SW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10C-SW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12C-SW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15C-SW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20C-SW-C	13.375 (340)	4.000 (102)	3.040 (77)	1.812 (46)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30C-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40C-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)

### TYPE LB



Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	H <sub>2</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07C-SW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10C-SW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12C-SW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15C-SW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20C-SW-LB	11.250 (286)	4.000 (102)	3.040 (77)	1.812 (46)	6.687 (170)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	4.508 (114)	425.00 (6964)	4.24 (1.92)

### TYPE LL



Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	W <sub>1</sub> inch (mm)	H <sub>1</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07C-SW-LL	7.375 (187)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10C-SW-LL	7.375 (187)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12C-SW-LL	9.000 (229)	2.875 (73)	2.540 (64)	4.500 (114)	1.188 (30)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15C-SW-LL	9.000 (229)	2.875 (73)	2.540 (64)	4.500 (114)	1.188 (30)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20C-SW-LL	11.250 (286)	4.000 (102)	3.040 (77)	5.500 (140)	1.812 (46)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-LL	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30C-SW-LL	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40C-SW-LL	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)