



STRAIGHT SOCKET (XW)

Type XW (Xtra Wall) Inches (Metric)									
Nominal Size	Item No. Aboveground	UL Listed	Outside Diameter		Min. Inside Diameter	Nominal Wall Thickness* (T)	Length (L)	Weight	
			Average	Tolerance				lbs/ft	kg/m
¾ (19)	07C-XW-10S	Yes	1.410 (36)	+0.056 (1.4) -0.036 (0.9)	0.910 (23)	.25 (6)	10 ft (3m)	.61 (0.91)	
1 (25)	10C-XW-10S	Yes	1.675 (43)	+0.056 (1.4) -0.036 (0.9)	1.175 (30)	.25 (6)	10 ft (3m)	.68 (1.01)	
1¼ (32)	12C-XW-20-S	Yes	2.020 (51)	+0.056 (1.4) -0.036 (0.9)	1.520 (39)	.25 (6)	20 ft (6.1m)	.82 (1.22)	
1½ (38)	15C-XW-20-S	Yes	2.260 (57)	+0.056 (1.4) -0.036 (0.9)	1.760 (45)	.25 (6)	20 ft (6.1m)	1.18 (1.76)	
2 (51)	20D-XW-20-S	Yes	2.500 (64)	+0.056 (1.4) -0.036 (0.9)	2.000 (51)	.25 (6)	20 ft (6.1m)	1.26 (1.88)	
2½ (64)	25D-XW-20-S	Yes	3.000 (76)	+0.056 (1.4) -0.036 (0.9)	2.500 (64)	.25 (6)	20 ft (6.1m)	1.54 (2.29)	
3 (76)	30D-XW-20-S	Yes	3.500 (89)	+0.056 (1.4) -0.036 (0.9)	3.000 (76)	.25 (6)	20 ft (6.1m)	1.82 (2.71)	
3½ (89)	35D-XW-20-S	Yes	4.000 (102)	-0.036 (1.4) +0.056 (0.9)	3.500 (89)	.25 (6)	20 ft (6.1m)	2.10 (3.13)	
4 (102)	40D-XW-20-S	Yes	4.500 (114)	+0.056 (1.4) -0.036 (0.9)	4.000 (102)	.25 (6)	20 ft (6.1m)	2.38 (3.54)	
5 (127)	50D-XW-20-S	Yes	5.500 (140)	+0.056 (1.4) -0.036 (0.9)	5.000 (127)	.25 (6)	20 ft (6.1m)	2.94 (4.38)	
6 (152)	60D-XW-20-S	Yes	6.500 (165)	+0.056 (1.4) -0.036 (0.9)	6.000 (152)	.25 (6)	20 ft (6.1m)	3.50 (5.21)	
8** (203)	80C-XW-20-S	--	8.900 (226)	+0.056 (1.4) -0.036 (0.9)	8.400 (213)	.25 (6)	20 ft (6.1m)	4.80 (7.14)	
10 (254)	100D-XW-20-S	--	10.500 (267)	+0.056 (1.4) -0.036 (0.9)	10.000 (254)	.25 (6)	20 ft (6.1m)	5.74 (8.54)	
12 (305)	120D-XW-20-S	--	12.500 (318)	+0.056 (1.4) -0.036 (0.9)	12.000 (305)	.25 (6)	20 ft (6.1m)	6.86 (10.21)	

* Actual wall thickness is that required to meet the performance requirements for specifications. Other wall thicknesses are available by special request.

** XW type conduit is also available with an inside diameter of 8.000 (203). Please contact our factory for further information.