

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

* 1 Identification

- **Product identifier**
- **Trade name: Epoxy Adhesive Part B**
- **Product number:**
CM-2020 Part B, CM-2040 Part B, CM-2070 Part B, CF-2020 Part B, CF-2040 Part B, & CF-2070 Part B
- **Relevant identified uses of the substance or mixture and uses advised against**
Part B of Epoxy Resin Compound
- **Product description** Epoxy Resin Curative
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Champion Fiberglass, Inc.
6400 Spring Stuebner Rd.
Spring, TX 77389
Phone: 281.655.8900
Fax: 281.257.2523
www.championfiberglass.com
- **Emergency telephone number:** 281.655.8900

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1A H350 May cause cancer.
Repr. 1B H360 May damage fertility or the unborn child.
STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.
Acute Tox. 4 H332 Harmful if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

 H227 Combustible liquid.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B**· Hazard pictograms**

GHS05 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labeling:**

2-piperazin-1-ylethylamine

Proprietary

Bisphenol A

Proprietary

Proprietary

· Hazard statements

Combustible liquid.

Harmful in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Do not breathe dusts or mists.

Use only outdoors or in a well-ventilated area.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO₂, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

38.3 percent of the mixture consists of ingredient(s) of unknown toxicity.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	*3	Health = *3
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

· **Other hazards** None known* **3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous Components:**

CAS: 140-31-8 RTECS: TK 8050000	2-piperazin-1-ylethylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; H227; Aquatic Chronic 3, H412	40-60%
RTECS: VV 7330000	Proprietary ⚠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	25-50%
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	2-12%
CAS: 80-05-7 RTECS: SL 6300000	Bisphenol A ⚠ Repr. 2, H361; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; STOT SE 3, H335	≤ 2.5%
	Proprietary ⚠ Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	≤ 2.5%
	Proprietary ⚠ Carc. 1B, H350	≤ 2.5%
RTECS: UY 5790000	Proprietary ⚠ Repr. 1B, H360; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≤ 2.5%

* **4 First-aid measures**· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

- **After inhalation:** In case of unconsciousness, place patient securely on side position for transportation.
- **After skin contact:**
May cause burn in case of contact with product at high temperature. Remove contaminated clothing and footwear and dispose of safely. Wash affected area with soap and water. Seek medical attention if skin irritation, swelling or redness develops or persists. If applicable, when using high pressure equipment, injection of product can occur. If high pressure injuries occur, immediately seek professional medical attention. For minor thermal burns, hold the burned area under cold running water for at least five minutes or until the pain subsides. However, body hypothermia must be avoided. Do not put ice on the burn. Remove non-sticking garments carefully. DO NOT attempt to remove portions of clothing glued to burnt skin but cut around them. Seek immediate medical attention in all cases of serious burns. Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
May cause burn in case of contact with product at high temperature. If hot product is splashed into the eye, it should be cooled immediately to dissipate heat, under cold running water. Immediately obtain specialist medical assessment and treatment for the casualty.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:**
Water spray or water fog. May cause frothing which can be violent, especially if sprayed into containers of hot or burning liquid.
- **Special hazards arising from the substance or mixture**
Combustible liquid. Vapors can travel to a source of ignition and flash back.
Explosive mixtures may occur at temperatures at or above flashpoint.
If product is incinerated it may release toxic fumes including: Oxides of Carbon, Nitrogen (NOx) Titanium and Silicon.
- **Advice for firefighters**
- **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Treat any fumes as toxic.
Mount respiratory protective device.
Do not breathe vapor.
Keep away from ignition sources
Keep people at a distance and stay upwind.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

- Dispose contaminated material as waste according to section 13.
- After material has been absorbed, area may be flushed with water or wet-brushed to clean.
- Ensure adequate ventilation.
- Dispose of the collected material according to regulations.
- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

*** 7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**
- Avoid contact with skin, eyes and clothing
- Keep away from sources of ignition.
- Use personal protection equipment as outlined in section 8.
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Keep receptacles tightly sealed.
- **Information about protection against explosions and fires:**
- Protect from heat.
- Protect against electrostatic charges.
- Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- Store away from acids, bases, strong oxidizing agents, strong reducing agents, Ammonia, Air, Hydrogen Fluoride, Oxygen difluoride and Chlorine trifluoride.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
- Keep receptacle tightly sealed.
- Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

*** 8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

Proprietary	
PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

Proprietary	
WEEL	Long-term value: 10 ppm Skin
Proprietary	
PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI
Proprietary	
ACGIH-TLV	Short-term value: 3 mg/m ³ Long-term value: 4 E mg/m ³
OSHA-PEL	Short-term value: 5 mg/m ³ Long-term value: 4 E mg/m ³
Proprietary	
PEL	Long-term value: 15* mg/m ³ *total dust
REL	See Pocket Guide App. A
TLV	Long-term value: 10 mg/m ³ withdrawn from NIC
· Ingredients with biological limit values:	
Proprietary	
BEI	100 mg/L urine end of shift 5-Hydroxy-N-methyl-2-pyrrolidone

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Respiratory protection is not required unless handling of the material produces nuisance airborne concentrations.

· **Protection of hands:**

Protective gloves

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:** Tightly sealed goggles

* 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Viscous liquid
Color: Creamy off-white

- **Odor:** Amine-like

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 220 °C (428 °F)

- **Flash point:** 77 °C (171 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 315 °C (599 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Not determined.

- **Explosion limits:**

Lower: 2.1 Vol %

Upper: 10.5 Vol %

- **Vapor pressure @ 20 °C (68 °F):** 0.1 hPa

- **Density @ 20 °C (68 °F):** 1.29 g/cm³ (10.765 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B**Kinematic:**

Not determined.

Other information

No further relevant information available.

*** 10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:**
Acids, bases, strong oxidizing agents, strong reducing agents, Ammonia, Air, Hydrogen Fluoride, Oxygen difluoride and Chlorine trifluoride.
- **Hazardous decomposition products:** Oxides of Carbon, Nitrogen (NOx) Titanium and Silicon.

*** 11 Toxicological information****Information on toxicological effects****Acute toxicity:****LD/LC50 values that are relevant for classification:****140-31-8 2-piperazin-1-ylethylamine**

Oral	LD50	2140 mg/kg (rat)
Dermal	LD50	880 mg/kg (rabbit)
Inhalative	LC50/4 h	100 mg/l (Trout)

80-05-7 Bisphenol A

Oral	LD50	3250 mg/kg (rat)
Dermal	LD50	3000 mg/kg (rabbit)

Proprietary

Oral	LD50	470 mg/kg (rat)
Dermal	LD50	220 mg/kg (rab)
Inhalative	LC50/4 h	2174.91 mg/l (rat)

Proprietary

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

Proprietary

Oral	LD50	10000 mg/kg (rat)
------	------	-------------------

Proprietary

Oral	LD50	3914 mg/kg (rat)
Dermal	LD50	8000 mg/kg (rabbit)

Primary irritant effect:**on the skin:**

Strong caustic effect on skin and mucous membranes.
May cause an allergic skin reaction.

on the eye:

Strong irritant with the danger of severe eye injury.
Corrosive effect.
Causes serious eye irritation.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Carcinogenic.
Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

Proprietary	1
Proprietary	3
Proprietary	2B
Proprietary	3
· NTP (National Toxicology Program)	
Proprietary	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

***12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

140-31-8 2-piperazin-1-ylethylamine	
EC50	32 mg/l (daphnia)
Proprietary	
EC50	1815 mg/l (Water flea)
Proprietary	
EC50	>1000 mg/l (Water flea)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

*** 13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:**
Disposal must be made according to official regulations.
Dispose of as unused product.

14 Transport information

- **UN-Number**
 - **DOT, ADR, IMDG, IATA**
 - **UN proper shipping name**
 - **DOT**
 - **ADR**
 - **IMDG, IATA**
 - **Transport hazard class(es)**
 - **DOT**
- UN2735
Polyamines, liquid, corrosive, n.o.s. (N-Aminoethylpiperazine, 2,4,6-tris(dimethylaminomethyl)phenol)
UN2735 Polyamines, liquid, corrosive, n.o.s. (N-Aminoethylpiperazine, 2,4,6-tris(dimethylaminomethyl)phenol)
POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N-AMINOETHYLPIPERAZINE, 2,4,6-tris(dimethylaminomethyl)phenol)



- **Class**
 - **Label**
- 8 Corrosive substances
8

- **ADR**



- **Class**
 - **Label**
- 8 (C7) Corrosive substances
8

- **IMDG, IATA**



- **Class**
 - **Label**
- 8 Corrosive substances
8

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

· Packing group	III
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN2735, Polyamines, liquid, corrosive, n.o.s. (N-Aminoethylpiperazine, 2,4,6-tris(dimethylaminomethyl)phenol), 8, III

***15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
--

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):
--

80-05-7	Bisphenol A
---------	-------------

	Proprietary
--	-------------

	Proprietary
--	-------------

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

Proprietary

Proprietary

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients are listed.

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

· Chemicals known to cause developmental toxicity:	
Proprietary	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
Proprietary	NL
· TLV (Threshold Limit Value established by ACGIH)	
Proprietary	A2
Proprietary	A4
Proprietary	A3
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
Proprietary	
Proprietary	

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS05 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

2-piperazin-1-ylethylamine

Proprietary

Bisphenol A

Proprietary

Proprietary

· **Hazard statements**

Combustible liquid.

Harmful in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.

Do not breathe dusts or mists.

Use only outdoors or in a well-ventilated area.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

(Contd. on page 13)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B

Do not eat, drink or smoke when using this product.
 Contaminated work clothing must not be allowed out of the workplace.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Wash contaminated clothing before reuse.
 IF exposed or concerned: Get medical advice/attention.
 If skin irritation or rash occurs: Get medical advice/attention.
 If swallowed: Rinse mouth. Do NOT induce vomiting.
 Get medical advice/attention if you feel unwell.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know

CAS: 140-31-8 RTECS: TK 8050000	2-piperazin-1-ylethylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; H227; Aquatic Chronic 3, H412	40-60%
RTECS: VV 7330000	Proprietary ⚠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	25-50%
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	2-12%
	Proprietary	2-12%
CAS: 80-05-7 RTECS: SL 6300000	Bisphenol A ⚠ Repr. 2, H361; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; STOT SE 3, H335	≤ 2.5%
	Proprietary ⚠ Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	≤ 2.5%
All ingredients are listed.		

· Information about limitation of use:

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

(Contd. on page 14)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/04/2015

Reviewed on 03/04/2015

Trade name: Epoxy Adhesive Part B· **Date of preparation / last revision** 03/04/2015 / -· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 : Flammable liquids, Hazard Category 4
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
 Carc. 1A: Carcinogenicity, Hazard Category 1A
 Carc. 1B: Carcinogenicity, Hazard Category 1B
 Carc. 2: Carcinogenicity, Hazard Category 2
 Repr. 1B: Reproductive toxicity, Hazard Category 1B
 Repr. 2: Reproductive toxicity, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106