

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

* 1 Identification

- **Product Identifier**
- **Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)**
- **Product Number:** CM-XXX-FG (where XXX is the package code.)
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:** Sealant/adhesive resin, Part B of 2-Part Adhesive
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Champion Fiberglass, Inc.
6400 Spring Stuebner Rd.
Spring, TX 77389
Phone: 281.655.8900
Fax: 281.257.2523
www.championfiberglass.com
- **Emergency telephone number:** 281.655.8900

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Skin Irritation 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Warning
- **Hazard-determining components of labeling:**
1,3-bis[3-(dimethylamino)propyl]urea
Polymer of c-18 unsat'd fatty acid dimers w/ teta & tofa
triethylenetetramine
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL
- **Hazard statements:**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- **Precautionary statements:**
P264 Wash thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

This value refers to knowledge of known, established toxicological or ecotoxicological values.

0 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	1	Physical Hazard = 1

· **Hazard(s) not otherwise classified (HNOC):** None known

* 3 Composition/Information on Ingredients

· **Chemical characterization: Substance**

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

68082-29-1	Polymer of c-18 unsat'd fatty acid dimers w/ teta & tofa ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	10-15%
52338-87-1	1,3-bis[3-(dimethylamino)propyl]urea ⚠ Eye Damage 1, H318; ⚠ Skin Irritation 2, H315; Sensitization - Skin 1, H317	3-7%
68541-13-9	Polymer of C-18 Unsaturated Fatty Acid Dimers ⚠ Eye Irritation 2A, H319	3-7%
112-24-3	triethylenetetramine ⚠ Skin Corrosion 1B, H314; ⚠ Acute Toxicity - Dermal 4, H312; Sensitization - Skin 1, H317	1-3%
4246-51-9	BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL ⚠ Eye Damage 1, H318; ⚠ Acute Toxicity - Dermal 4, H312	1-3%

· **Non-hazardous components:**

No additional ingredients require reporting based on applicable concentration and current supplier knowledge.

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· **Description of first aid measures**

· **General information:** If symptoms persist, call a physician.

· **After inhalation:**

If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.

· **After skin contact:**

Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.

· **After eye contact:** Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

· **After swallowing:**

Wash out mouth with water. Do not induce vomiting. If victim is unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

5 Fire-Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, sand, dry chemical, water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information.

· **Special hazards arising from the substance or mixture:**

Dense smoke is emitted when burned without sufficient oxygen.

Oxides of carbon, oxides of sulfur, oxides of nitrogen. May contain other combustion products of varying composition which may be toxic or irritating.

· **Advice for firefighters**

· **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

* 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:**

Isolate area. Use appropriate safety equipment.

· **Environmental precautions:**

Dilute with plenty of water.

Avoid release to the environment.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **PAC-1:**

112-24-3	triethylenetetramine	3 ppm
4246-51-9	BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	13 mg/m ³

· **PAC-2:**

112-24-3	triethylenetetramine	14 ppm
4246-51-9	BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	140 mg/m ³

· **PAC-3:**

112-24-3	triethylenetetramine	83 ppm
----------	----------------------	--------

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

4246-51-9	BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL
-----------	---

850 mg/m ³

* 7 Handling and Storage

- **Handling**

- **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s):** No further relevant information available.

* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

- **Components with occupational exposure limits:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

112-24-3 triethylenetetramine

WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile, neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

· **Limitation and supervision of exposure into the environment:** None

* 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Gel
· Color:	White to yellow
· Odor:	Slight sulfur, pungent
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	Not determined.

· **Flash point:** ≥ 90 °C (≥ 194 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Auto igniting:** Not applicable

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not self-igniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· Lower:	Not determined.
-----------------	-----------------

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

Upper:	Not determined.
· Vapor pressure @ 20 °C (68 °F):	<1 mmHg
· Density @ 20 °C (68 °F):	1.17 g/cm ³ (9.7637 lbs/gal)
· Relative density:	Not determined.
· Vapor density:	Not determined.
· Evaporation rate:	Not determined.
· Solubility in / Miscibility with:	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.00 %
· Other information:	No further relevant information available.

* 10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Product is stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Avoid extreme heat and open flame.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:**
Oxides of carbon, oxides of sulfur, oxides of nitrogen and other organic substances may be formed during combustion or elevated temperature degradation.

* 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

LD/LC50 values that are relevant for classification:		
52338-87-1 1,3-bis[3-(dimethylamino)propyl]urea		
Oral	LD50	2,050 mg/kg (Rat)
112-24-3 triethylenetetramine		
Oral	LD50	2,500 mg/kg (Rat)
Dermal	LD50	805 mg/kg (rabbit)

- **Primary irritant effect:**

- **On the skin:**

Irritant to skin and mucous membranes.
May cause an allergic skin reaction.

- **On the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

· **Carcinogenic categories:**

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

* 12 Ecological Information

· **Toxicity:**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods**

· **Recommendation:**

Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packaging**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport Information

· **UN-Number:**

· **DOT, ADR/ADN, IMDG, IATA**

Non-Regulated Material

· **UN proper shipping name:**

· **DOT, IMDG, IATA**

Non-Regulated Material

· **ADR/ADN**

UN-

· **Transport hazard class(es):**

· **DOT, ADR/ADN, ADN, IMDG, IATA**

· **Class:**

Non-Regulated Material

· **Packing group:**

· **DOT, ADR/ADN, IMDG, IATA**

Non-Regulated Material

· **Environmental hazards:**

Not applicable.

· **Special precautions for user:**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:**

Not applicable.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

· **UN "Model Regulation":** Non-Regulated Material

* 15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients are listed.

· **California Proposition 65:**

WARNING: This product can expose you to chemicals including sulphuric acid, nitrilotriacetic acid, which is/are known to the State of California to cause cancer. For more information, go to www.p65warnings.ca.gov.

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **New Jersey Right-to-Know List:**

112-24-3 triethylenetetramine

· **New Jersey Special Hazardous Substance List:**

112-24-3 triethylenetetramine

CO

· **Pennsylvania Right-to-Know List:**

112-24-3 triethylenetetramine

· **Pennsylvania Special Hazardous Substance List:**

None of the ingredients are listed.

· **Carcinogenic categories:**

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)

· **Hazard pictograms:**



· **Signal word:** Warning

· **Hazard-determining components of labeling:**

1,3-bis[3-(dimethylamino)propyl]urea
 Polymer of c-18 unsat'd fatty acid dimers w/ teta & tofa
 triethylenetetramine
 BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL

· **Hazard statements:**

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

· **Precautionary statements:**

P264 Wash thoroughly after handling.
 P280 Wear protective gloves / eye protection / face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Contact:**

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety and Health

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/07/2024

Reviewed on 07/07/2024

Trade Name: **Fiberglass Conduit Epoxy Adhesive CM-600-FG/CM-250-FG (Part B)**

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Dermal 4: Acute toxicity – Category 4

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106