


## CONDUIT BODIES


All conduit bodies are manufactured by compression molding for ultimate strength. The conduit bodies are made of vinyl ester resin with high glass content, flame retardant per UL 2515 and CSA C22.2 No. 2515 and halogen free. Each conduit body is supplied with a high performance rubber gasket to provide a water tight seal between the cover and conduit body. Provided hardware is stainless steel.

### TYPE C




Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07C-SW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10C-SW-C	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12C-SW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15C-SW-C	10.125 (257)	2.875 (73)	2.540 (64)	1.188 (30)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20C-SW-C	13.375 (340)	4.000 (102)	3.040 (77)	1.812 (46)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30C-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40C-SW-C	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)

### TYPE LB




Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	H <sub>1</sub> inch (mm)	H <sub>2</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07C-SW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10C-SW-LB	7.375 (187)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12C-SW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15C-SW-LB	9.000 (229)	2.875 (73)	2.540 (64)	1.188 (30)	4.875 (124)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20C-SW-LB	11.250 (286)	4.000 (102)	3.040 (77)	1.812 (46)	6.687 (170)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40C-SW-LB	16.125 (410)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	4.508 (114)	425.00 (6964)	4.24 (1.92)

### TYPE LL




Nominal Size	Type	IPS Item No. Aboveground	L inch (mm)	H inch (mm)	W inch (mm)	W <sub>1</sub> inch (mm)	H <sub>1</sub> inch (mm)	D inch (mm)	Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
¾	SW	07C-SW-LL	7.375 (187)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)
1	SW	10C-SW-LL	7.375 (187)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)
1¼	SW	12C-SW-LL	9.000 (229)	2.875 (73)	2.540 (64)	4.500 (114)	1.188 (30)	1.685 (43)	32.00 (524)	1.20 (0.54)
1½	SW	15C-SW-LL	9.000 (229)	2.875 (73)	2.540 (64)	4.500 (114)	1.188 (30)	1.910 (48)	32.00 (524)	1.10 (0.50)
2	SW	20C-SW-LL	11.250 (286)	4.000 (102)	3.040 (77)	5.500 (140)	1.812 (46)	2.390 (61)	70.75 (1160)	2.50 (1.13)
2½	SW	25C-SW-LL	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
3	SW	30C-SW-LL	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)
4	SW	40C-SW-LL	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)

**TYPE LR**




Nominal Size	Type	IPS Item No. Aboveground	L		H		W		W <sub>1</sub>		H <sub>1</sub>		D		Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
			inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)				
¾	SW	07C-SW-LR	7.375 (187)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)						
1	SW	10C-SW-LR	7.375 (187)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)						
1¼	SW	12C-SW-LR	9.000 (229)	2.875 (73)	2.540 (64)	4.500 (114)	1.188 (30)	1.685 (43)	32.00 (524)	1.20 (0.54)						
1½	SW	15C-SW-LR	9.000 (229)	2.875 (73)	2.540 (64)	4.500 (114)	1.188 (30)	1.910 (48)	32.00 (524)	1.10 (0.50)						
2	SW	20C-SW-LR	11.250 (286)	4.000 (102)	3.040 (77)	5.500 (140)	1.812 (46)	2.390 (61)	70.75 (1160)	2.50 (1.13)						
2½	SW	25C-SW-LR	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
3	SW	30C-SW-LR	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
4	SW	40C-SW-LR	16.125 (410)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)						

**TYPE T**




Nominal Size	Type	IPS Item No. Aboveground	L		H		W		W <sub>1</sub>		H <sub>1</sub>		D		Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
			inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)				
¾	SW	07C-SW-T	8.375 (213)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)						
1	SW	10C-SW-T	8.375 (213)	2.375 (60)	1.840 (47)	3.500 (89)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)						
1¼	SW	12C-SW-T	10.125 (257)	3.000 (76)	2.540 (64)	4.437 (113)	1.188 (30)	1.685 (43)	32.00 (524)	1.40 (0.64)						
1½	SW	15C-SW-T	10.125 (257)	3.000 (76)	2.540 (64)	4.437 (113)	1.188 (30)	1.910 (48)	32.00 (524)	1.30 (0.59)						
2	SW	20C-SW-T	13.375 (340)	4.000 (102)	3.040 (77)	5.500 (140)	1.812 (46)	2.390 (61)	70.75 (1160)	2.80 (1.27)						
2½	SW	25C-SW-T	21.750 (552)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
3	SW	30C-SW-T	21.750 (552)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
4	SW	40C-SW-T	21.750 (552)	6.000 (152)	5.875 (149)	8.750 (222)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)						

**TYPE TB**



Nominal Size	Type	IPS Item No. Aboveground	L		H		W		H <sub>1</sub>		H <sub>2</sub>		D		Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
			inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)				
¾	SW	07C-SW-TB	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.075 (27)	13.90 (228)	0.70 (0.32)						
1	SW	10C-SW-TB	8.375 (213)	2.375 (60)	1.840 (47)	1.000 (25)	3.900 (99)	1.340 (34)	13.90 (228)	0.70 (0.32)						
1¼	SW	12C-SW-TB	10.125 (257)	3.000 (76)	2.540 (64)	1.188 (30)	4.875 (124)	1.685 (43)	32.00 (524)	1.40 (0.64)						
1½	SW	15C-SW-TB	10.125 (257)	3.000 (76)	2.540 (64)	1.188 (30)	4.875 (124)	1.910 (48)	32.00 (524)	1.30 (0.59)						
2	SW	20C-SW-TB	13.375 (340)	4.000 (102)	3.040 (77)	1.812 (46)	6.687 (170)	2.390 (61)	70.75 (1160)	2.80 (1.27)						
2½	SW	25C-SW-TB	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
3	SW	30C-SW-TB	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
4	SW	40C-SW-TB	21.750 (552)	6.000 (152)	5.875 (149)	3.000 (76)	8.750 (222)	4.508 (114)	425.00 (6964)	4.24 (1.92)						

**TYPE X**



Nominal Size	Type	IPS Item No. Aboveground	L		H		W		W <sub>1</sub>		H <sub>1</sub>		D		Volume cu in (cm <sup>3</sup> )	Weight lbs (kg)
			inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)				
¾	SW	07C-SW-X	8.375 (213)	2.375 (60)	1.840 (47)	4.750 (121)	1.000 (25)	1.075 (27)	13.90 (228)	0.70 (0.32)						
1	SW	10C-SW-X	8.375 (213)	2.375 (60)	1.840 (47)	4.750 (121)	1.000 (25)	1.340 (34)	13.90 (228)	0.70 (0.32)						
1¼	SW	12C-SW-X	10.125 (257)	3.000 (76)	2.540 (64)	6.437 (163)	1.188 (30)	1.685 (43)	32.00 (524)	1.60 (0.73)						
1½	SW	15C-SW-X	10.125 (257)	3.000 (76)	2.540 (64)	6.437 (163)	1.188 (30)	1.910 (48)	32.00 (524)	1.50 (0.68)						
2	SW	20C-SW-X	13.375 (340)	4.000 (102)	3.040 (77)	7.188 (182)	1.812 (46)	2.390 (61)	70.75 (1160)	3.00 (1.36)						
2½	SW	25C-SW-X	21.750 (552)	6.000 (152)	5.875 (149)	11.500 (292)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
3	SW	30C-SW-X	21.750 (552)	6.000 (152)	5.875 (149)	11.500 (292)	3.000 (76)	3.508 (89)	425.00 (6964)	4.24 (1.92)						
4	SW	40C-SW-X	21.750 (552)	6.000 (152)	5.875 (149)	11.500 (292)	3.000 (76)	4.508 (114)	425.00 (6964)	4.24 (1.92)						